















KOMET

Innovative, flexible and space-saving design

Kiosk in portrait format for an optimized customer experience

KOMET is an interactive and multi-function touch solution, an indispensable kiosk equipment to optimize fluidity and speed up service times to guarantee a successful Customer Experience.

With a sober and elegant design, available in 3 versions (Single-sided, Double-sided and Wall-mounted), it can be integrated into most commercial environments, from Catering and Hospitality to Retail, Leisure and Services.

KOMET integrates high-performance and flexible OEM equipment, such as a YUNO Kiosk 27" system in portrait mode, an ODP 444 ticket printer, a payment terminal and a 2D imager barcode scanner. An indicator light, positioned at the top of the kiosk, allows instant identification of its operating status and distinct monitoring of the different assistance needs of the customer (user assistance, end of paper in the printer, alerts if necessary, etc).

Whatever the chosen configuration, the KOMET kiosk offers an adapted footprint, significantly reducing the space requirement within the point of sale. This space saving is an opportunity to increase the number of kiosks and thus enhance the perceived quality of service.











KOMET

Single, double-sided or wall-mounted kiosk (small footprint) Portrait Mode touch screen (YUNO 27") for dynamic order taking Projected capacitive multi-touch panel (PCAP - 10 points)

3 processors to choose from: i5, i3 or J1900 $\,$

128 GB 2.5" SSD

4 GB memory as standard, expandable to 8 GB

ODP 444 thermal receipt printer (80 mm)

1D/2D imager barcode reader

Integrated payment terminal: electronic payment modularity (adapter plate to integrate a wide range of PED - Valina VX/P400 - Lane/ IPP - S300)

Integrated status light indicator (optional)









Control of the last of the las	YUNO	174114354	
3131EN		14 1 1 2 2 2 3	

Processor	i5-5350U, i3 -5010U Broadwell or Intel Bay Trail J1900
Memory	DDR3 SODIMM 4 GB in standard (up to 8 GB)
SSD	2,5" 128 GB (2 slots)
LCD	27" TFT Full HD (1920 x 1080)
Touch screen	Flat & Edgeless PCAP Panel

OTHER SYSTEMS	
1D/2D Scanner	Datalogic 1500i
Printer	ODP 444 thermal receipt printer
LED Lighting	USB electronic card control (3 colours)

INPUTS/OUTPUTS

Serial ports	4 ports (+ power supply 5/12 V for COM3 / COM4)	
USB	5 x USB 2.0 + 1 x USB 3.0 (J1900 version) 4 x USB 2.0 + 2 USB 3.0 (i5 & i3 versions)	
LAN	10/100/1000 Base-T	
Audio	Internal loudspeaker, headphones / microphone jack	

PAYMENT TERMINALS

Ingenico	LANE 5000 / LANE 3000 / IPP 350
Verifone	P400 / VX820
PAX	S 300

	-	ELL			
100	-		C		100
				_	

CEM	CE Directive CEM 2014/30/EU (Class B)	
Safety	CE Directive BT 2014/35/EU / CB Report	
Operating temperature	5 - 35° C	
Front Panel	Splash & Dust Resistant (IP54)	
Colours	Black (other colours upon request - minimum order quantity 100 units)	
Compatibles OS	Windows 10 IoT Enterprise, Linux	
Dimensions (W x D X H)	single: 39.3 x 18.5 x 178 double: 39.3 x 23.9 x 178 wall: 39.3 x 18.5 x	
106 Weight (kg)	single: 70 (incl. pedestal) double: 94 (incl. pedestal) wall: 50 kg	
Options	Standing plate 78,5 x 78,5 x 1 cm / 49 kg Pedestal (single sided / double sided) Wall fixing kit (wall mounted)	



www.ldapos.es